

BPharm Semester IV - End Semester Examination, July 2021

PCE-BP403T: Physical Pharmaceutics II (Theory)

I Multiple Choice Questions (MCQs) 1 is mainly measured by Nephelometer for the determination of turbidity A. Absorbed light B. Transmitted light C. Scattered light D. Incident light 2. Peptization method is mainly used to prepare colloid. A. Lyophilic B. Lyophobic C. Association D. Lyophilic and Association	Date:	Duration:	Max. Marks: 50
I is mainly measured by Nephelometer for the determination of turbidity A. Absorbed light B. Transmitted light C. Scattered light D. Incident light C. Peptization method is mainly used to preparecolloid. A. Lyophilic B. Lyophobic C. Association D. Lyophilic and Association B. Between 1 nm B. Between 1 nm B. Between 1 nm D. Between 1000 to 2000 nm C. More than 500 nm D. Between 1000 to 2000 nm Elastic deformation of solids is governed by A. Newton's law B. Stokes law C. Hooke's law D. Fick's law Ostwald viscometer is mainly used to determine viscosity of liquids A. Newtonian B. Plastic C. Pseudoplastic D. Dilatant is a multi-point viscometer that can operate at different rates of shear: A. Capillary viscometer B. Falling sphere viscometer			
I is mainly measured by Nephelometer for the determination of turbidity A. Absorbed light B. Transmitted light C. Scattered light D. Incident light C. Peptization method is mainly used to preparecolloid. A. Lyophilic B. Lyophobic C. Association D. Lyophilic and Association B. Between 1 nm B. Between 1 nm B. Between 1 nm D. Between 1000 to 2000 nm C. More than 500 nm D. Between 1000 to 2000 nm Elastic deformation of solids is governed by A. Newton's law B. Stokes law C. Hooke's law D. Fick's law Ostwald viscometer is mainly used to determine viscosity of liquids A. Newtonian B. Plastic C. Pseudoplastic D. Dilatant is a multi-point viscometer that can operate at different rates of shear: A. Capillary viscometer B. Falling sphere viscometer	I Multiple Chains On the	(MEGO.)	1 11
B. Transmitted light C. Scattered light D. Incident light D. Incident light C. Speciation method is mainly used to preparecolloid. A. Lyophilic B. Lyophobic C. Association D. Lyophilic and Association B. Elyophilic and Association C. More than 500 nm C. More than 500 nm D. Between 1nm to 500 nm D. Between 1000 to 2000 nm D. Between 1000 to 2000 nm C. More than 500 mm D. Between 1000 to 2000 nm D. Between 1000 to 2000 nm C. More than 500 nm D. Between 1000 to 2000 nm D	1 wattiple Choice Questions	(MCQs)	
B. Transmitted light C. Scattered light D. Incident light D. Incident light C. Speciation method is mainly used to preparecolloid. A. Lyophilic B. Lyophobic C. Association D. Lyophilic and Association B. Elyophilic and Association C. More than 500 nm C. More than 500 nm D. Between 1nm to 500 nm D. Between 1000 to 2000 nm D. Between 1000 to 2000 nm C. More than 500 mm D. Between 1000 to 2000 nm D. Between 1000 to 2000 nm C. More than 500 nm D. Between 1000 to 2000 nm D	is mair	nly measured by Nephelometer for t	the determination of turbidity
C. Scattered light D. Incident light D. Incident light D. Incident light D. Incident light C. Peptization method is mainly used to prepare	- Table		turbuny
D. Incident light 2. Peptization method is mainly used to preparecolloid. A. Lyophilic B. Lyophobic C. Association D. Lyophilic and Association 3 is the particle size range of colloidal dispersions A. Less than 1 nm B. Between 1nm to 500 nm C. More than 500 nm D. Between 1000 to 2000 nm Elastic deformation of solids is governed by A. Newton's law B. Stokes law C. Hooke's law D. Fick's law Ostwald viscometer is mainly used to determine viscosity of liquids A. Newtonian B. Plastic C. Pseudoplastic D. Dilatant is a multi-point viscometer that can operate at different rates of shear: A. Capillary viscometer B. Falling sphere viscometer			
2. Peptization method is mainly used to prepare			
B. Lyophobic C. Association D. Lyophilic and Association 3	D. Incident light		
B. Lyophobic C. Association D. Lyophilic and Association 3	2. Peptization method is mainly	used to prepare	colloid.
C. Association D. Lyophilic and Association B	11. Lyopinic		
D. Lyophilic and Association a is the particle size range of colloidal dispersions A. Less than 1 nm B. Between 1nm to 500 nm C. More than 500 nm D. Between 1000 to 2000 nm Elastic deformation of solids is governed by A. Newton's law B. Stokes law C. Hooke's law D. Fick's law Ostwald viscometer is mainly used to determine viscosity of liquids A. Newtonian B. Plastic C. Pseudoplastic D. Dilatant is a multi-point viscometer that can operate at different rates of shear: A. Capillary viscometer B. Falling sphere viscometer			
A. Less than 1 nm B. Between 1nm to 500 nm C. More than 500 nm D. Between 1000 to 2000 nm Elastic deformation of solids is governed by A. Newton's law B. Stokes law C. Hooke's law D. Fick's law Ostwald viscometer is mainly used to determine viscosity of liquids A. Newtonian B. Plastic C. Pseudoplastic D. Dilatant is a multi-point viscometer that can operate at different rates of shear: A. Capillary viscometer B. Falling sphere viscometer			
A. Less than 1 nm B. Between 1nm to 500 nm C. More than 500 nm D. Between 1000 to 2000 nm Elastic deformation of solids is governed by A. Newton's law B. Stokes law C. Hooke's law D. Fick's law Ostwald viscometer is mainly used to determine viscosity of	D. Lyophilic and Association	on	
B. Between 1nm to 500 nm C. More than 500 nm D. Between 1000 to 2000 nm Elastic deformation of solids is governed by A. Newton's law B. Stokes law C. Hooke's law D. Fick's law Ostwald viscometer is mainly used to determine viscosity of liquids A. Newtonian B. Plastic C. Pseudoplastic D. Dilatant is a multi-point viscometer that can operate at different rates of shear: A. Capillary viscometer B. Falling sphere viscometer	3 is the	particle size range of colloidal disma	31
C. More than 500 nm D. Between 1000 to 2000 nm Elastic deformation of solids is governed by A. Newton's law B. Stokes law C. Hooke's law D. Fick's law Ostwald viscometer is mainly used to determine viscosity of liquids A. Newtonian B. Plastic C. Pseudoplastic D. Dilatant is a multi-point viscometer that can operate at different rates of shear: A. Capillary viscometer B. Falling sphere viscometer	A. Less man I mm		ersions
D. Between 1000 to 2000 nm Elastic deformation of solids is governed by A. Newton's law B. Stokes law C. Hooke's law D. Fick's law Ostwald viscometer is mainly used to determine viscosity of liquids A. Newtonian B. Plastic C. Pseudoplastic D. Dilatant is a multi-point viscometer that can operate at different rates of shear: A. Capillary viscometer B. Falling sphere viscometer		n	
Blastic deformation of solids is governed by A. Newton's law B. Stokes law C. Hooke's law D. Fick's law Ostwald viscometer is mainly used to determine viscosity of			
B. Stokes law C. Hooke's law D. Fick's law Ostwald viscometer is mainly used to determine viscosity ofliquids A. Newtonian B. Plastic C. Pseudoplastic D. Dilatant is a multi-point viscometer that can operate at different rates of shear: A. Capillary viscometer B. Falling sphere viscometer	D. Between 1000 to 2000 n	m	
B. Stokes law C. Hooke's law D. Fick's law Ostwald viscometer is mainly used to determine viscosity ofliquids A. Newtonian B. Plastic C. Pseudoplastic D. Dilatant is a multi-point viscometer that can operate at different rates of shear: A. Capillary viscometer B. Falling sphere viscometer	1. Elastic deformation of solids i	s governed by	
C. Hooke's law D. Fick's law Ostwald viscometer is mainly used to determine viscosity of liquids A. Newtonian B. Plastic C. Pseudoplastic D. Dilatant is a multi-point viscometer that can operate at different rates of shear: A. Capillary viscometer B. Falling sphere viscometer	A. Newton's law	governed by	
Ostwald viscometer is mainly used to determine viscosity ofliquids A. Newtonian B. Plastic C. Pseudoplastic D. Dilatant is a multi-point viscometer that can operate at different rates of shear: A. Capillary viscometer B. Falling sphere viscometer	B. Stokes law		
Ostwald viscometer is mainly used to determine viscosity ofliquids A. Newtonian B. Plastic C. Pseudoplastic D. Dilatant is a multi-point viscometer that can operate at different rates of shear: A. Capillary viscometer B. Falling sphere viscometer	C. Hooke's law		
B. Plastic C. Pseudoplastic D. Dilatant is a multi-point viscometer that can operate at different rates of shear: A. Capillary viscometer B. Falling sphere viscometer	D. Fick's law		
B. Plastic C. Pseudoplastic D. Dilatant is a multi-point viscometer that can operate at different rates of shear: A. Capillary viscometer B. Falling sphere viscometer	. Ostwald viscometer is mainly	ugod to data	
B. Plastic C. Pseudoplastic D. Dilatant is a multi-point viscometer that can operate at different rates of shear: A. Capillary viscometer B. Falling sphere viscometer	A. Newtonian	used to determine viscosity of	liquids
C. Pseudoplastic D. Dilatant is a multi-point viscometer that can operate at different rates of shear: A. Capillary viscometer B. Falling sphere viscometer			
D. Dilatant is a multi-point viscometer that can operate at different rates of shear: A. Capillary viscometer B. Falling sphere viscometer			
is a multi-point viscometer that can operate at different rates of shear: A. Capillary viscometer B. Falling sphere viscometer			
B. Falling sphere viscometer		pulti-point viscometer 4	
B. Falling sphere viscometer	15 a H	dun-poun viscometer that can opera	ate at different rates of shear:
C. Ostwald viscometer	B. Falling sphere viscometer		
	C. Ostwald viscometer		

15 D :
15. During storage, crystal growth is observed in suspension due to A. Absorption of water
B. Fluctuation in the ambient temperature
C. Presence of suspending agent
D. Volatilization of solids
16. Catalyst is a substance
A. Which controls the rate of reaction with partial change
B. Which changes the rate of reaction with itself completely undergoing a permanent chemical
change
C. Which controls the rate of reaction without itself undergoing a permanent chemical change D. None of the above
17. Arrhenius equation is used to explain:
A. Potential energy
B. Kinetic energy
C. Activation energy
D. Surface free energy
18. Boyle's law expresses the effect of on rate of reaction. A. Pressure
B. Catalyst
C. Temperature
D. Light
19. The specific rate constant (K) determined for aspirin hydrolysis in pH 1.0 buffer at 1 mg/mL
concentration is 5.0×10^{-5} min ⁻¹ at 25 °C. The shelf-life (in min) of the product is:
A. 20
B. 21 C. 100
D. 139
20. Degradation of drugs due to exposure of light is known as
A. Racemization
B. Solvolysis
C. Photolysis
D. Pyrolysis
II Short Answers Question
1. Explain DLVO theory with potential energy versus particle distance curve.
2. Compare and contrast pseudoplastic and dilatant flow of liquids.
Ans: Each point carries ONE marks.
3. Discuss the theories of emulsification.
Ans: Details of various theories of emulsification carries FIVE marks.
4. Explain the differences between flocculated and deflocculated suspensions.
Ans: Each difference carries ONE mark.
5. Discuss in detail the optical microscopy method for the determination of particle size.
6. Explain effect of hydrolysis on the stability of drugs with their preventive methods.