



MANIPAL INSTITUTE OF TECHNOLOGY

MANIPAL
(A constituent unit of MAHE, Manipal)

MANIPAL INSTITUTE OF TECHNOLOGY

M. TECH (STRUCTURAL ENGINEERING)

END SEMESTER EXAMINATION (MAKEUP), JUNE 2024

DESIGN OF PRESTRESSED CONCRETE STRUCTURES (CIE 5217)

(13 – 06 - 2024)

TIME: 3HRS.

MAX. MARKS: 50

Note: 1. Answer all questions.

2. IS:1343-2012 is permitted.

Q. NO	QUESTION	MARK	CO	BL
1A	Design a Type 1 rectangular post tensioned prestressed beam of size 320×640 mm cross section and span 14m. M45 grade concrete is used, and the tendons are initially prestressed to 76% of its characteristic strength ($f_{pk} = 1780$ MPa). A live load of 16 kN/m acts throughout the span of the beam and loss of prestress is 15%.	7	1	5
1B	A pretensioned one way simply supported slab of span 4.0m has a thickness of 130 mm and is prestressed with 6 no. of 7 mm diameter wires with initial prestress of 300 kN for every 1m length having 15 % loss of prestress at service. A total load (inclusive of self-weight) of 5.6 kN/m^2 acts on the slab. If $f_{pk} = 1620$ MPa and initial prestress is $0.75f_{pk}$ and M40 grade of concrete is used, compute the shear capacity of the section and check whether shear reinforcement is required.	3	4	4
2	A simply supported post tensioned flanged beam of span 7m having top flange 420×130 mm and web of 130×700 mm is subjected to a live load of 10 kN/m acting throughout the span. Steel tendon having zero eccentricity at support and 230 mm eccentricity at midspan is made of 9 no. of 7mm diameter wires having parabolic profile with characteristic strength 1720 MPa and effective prestress of 1045 MPa. Evaluate the ultimate flexural strength (M_{UR}) of the beam and check for serviceability limits at working and long term according to IS:1343-2012 specifications. Take $\Phi = 1.5$, M45 grade of concrete and loss of prestress as 20%.	10	2	5
3	A two span post-tensioned Type1 PSC continuous beam ABC, with span AB = 12 m and BC = 10 m has symmetrical section with flange 420×120 mm and web 160×560 mm, having $I = 14.115 \times 10^9 \text{ mm}^4$. M45 grade of concrete is used along with a concordant cable profile carrying an effective prestressing force of 800kN. Evaluate the critical stresses at service for a case of live load	10	3	5

	10 kN/m acting throughout the span, taking 20% loss of prestress, and check whether they are within the permissible limits prescribed by IS:1343-2012.			
4	Design a simply supported post tensioned one-way slab of 4.5 m span carrying a live load of 2.2 kN/m ² and finish load of 1.2 kN/m ² . Take M40 grade of concrete, 7 mm wires having characteristic strength of tendon 1650 MPa, initial prestress of 1200 MPa, 15% loss of prestress and (span/d) ratio of 45. Provide the transverse reinforcement details.	10	4	5
5	A composite T beam is made up of a pre-tensioned rib 180 mm thick and 360 mm deep, a cast-in-situ slab of 140 mm thickness and flange width for composite action can be taken as 700 mm. The beam is simply supported over a of span 6 m supporting a live load of 14 kN/m. Assume M40 grade of concrete in precast web and slab, high strength wires with initial prestress as $0.76f_{pk}$ (characteristic strength $f_{pk} = 1720$ MPa) and long term loss as 15%. Design the composite section and compute the stresses in the critical section at various stages. The precast member is unpropped during the casting of the CIP portion.	10	5	5